

Introductions for LED stage lighting

30W Mini Moving Head Gobo Light

(with light strips)



Please read the instructions carefully before use

Function Description

Addr	A001-A512	512 Address setting
CHnd	12CH	12 channel setting
	10CH	10 channel setting
SLnd	Auto	Host mode
	SL 1	Console mode
	SL 2	Secondary mode
SHnd	SH 0	Effect 0 (recommended)
	SH 1	Effect 1
	SH 2	Effect 2
	SH 3	Effect 3
Soud	on	Voice activated
	oFF	Voice off
SEnS	0-99	Voice-activated sensitivity adjustment
bLnd	bLAc	No 512 signal return to zero
	Auto	No 512 signal self-propelled
	Soun	No 512 signal sound
	HoLd	No 512 signal keeps last console state
LEd	OFF	After 5 seconds off the screen
	ON	The screen is always on
dISP	no	Display reverse
	YES	Display positive
rPAN	no	X motor forward
	YES	X motor reversal
rTiL	no	Y motor forward
	YES	Y motor reversal
REST	YES	System reset

12 Channel

Channel	Features	Instructions
1	Horizontal operation	0-255
2	Horizontal fine-tune	0-255
3	Vertical operation	0-255
4	Vertical fine-tune	0-255
5	color	0-9 White
		10-139 Color selection
		140-255 Automatic color change from slow to fast
6	Gobo	0-7 White
		8-63 Fixed gobo
		64-127 Shaking gobo
		128-255 Automatic change pattern from slow to fast
7	strobe	0-255
8	Dimming	0-255
9	Motor speed	0-255 from fast to slow
10	Automatic mode	0-59 Other channels function
		60-84 Automatic mode3
		85-109 Automatic mode2
		110-134 Automatic model
		135-159 Automatic modeO
		160-184 Voice-control mode3
		185-209 Voice-control mode2
		210-234 Voice-control model
		235-255 Voice-control modeO
11	reset	250-255 (5S)
12	Light strips	5-109 Color selection
		110-255 Color auto operation

10 Channel

Channel	Features	Instructions
1	Horizontal operation	0-255
2	Vertical operation	0-255
3	color	0-9 White
		10-139 Color selection
		140-255 Automatic color change from slow to fast
4	Gobo	0-7 White
		8-63 Fixed gobo
		64-127 Shaking gobo
		128-255 Automatic change pattern from slow to fast
5	strobe	0-255
6	Dimming	0-255
7	Motor speed	0-255
8	Automatic mode	0-59 Other channels function
		60-159 Automatic mode
		160-255 Voice-control mode
9	Reset	250-255 (5 seconds)
10	Light strips	5-109 Color selection
		110-255 Color auto operation

Specification:

Voltage: AC 100-240V, 50-60HZ

Power consumption: 60W

Light Source: 1PCS*30W White LED+ 12 RGB 0.2W lamp beads

Gobos: lwhite+7 gobos

Color: lwhite+7 colors

Channel: 10/12CH

Operation: DMX, Sound, Master-slave, Auto

Tilt: 540° Pan: 270°